MARK Hawk

Descender device with 2 eye bolts / EN 341

MARK Hawk is a Personal Protective Equipment (PPE) against falls from a height and has been designed for use in combination with PPE certified according to EN 361, EN 1497, EN 1498, EN 795 and EN 362. MARK Hawk is certified according to EN 341 and has been tested by TÜV Austria.





Who needs MARK Hawk?

MARK Hawk has been designed for professional users, e.g. fire services, height rescue, industrial climbers etc.

Key data

- Descent load: min. 30kg
- Descent load: max. 150kg
- Descent speed: ca. o.8m/sec
- Descent speed adjustable via eye bolts
- 10 years maintenance-free (original packaging)
- Steel housing
- Light metal carabiner
- Polyamide kernmantle rope

Braking system - maximum safety

MARK Hawk comes with a redundant braking system. The brake drums are made of steel. This ensures maximum safety while you are descending.

Inspection

MARK Hawk has to be inspected after 2,000m or after being subjected to major loads (e.g. after a rescue deployment) by MARK Save A Life or by a competent person.

Use

MARK Hawk is being used successfully worldwide: for height rescue, mountain rescue, by fire services and SWAT teams, for cave rescue, industrial climbing, in climbing and outdoor parks etc.

Combination with MARK products

MARK Hawk should be used only in combination with PPE certified according to the respective EN norms. We recommend the use as rescue system in combination with MARK Mammoth safety overall and/or MARK Grizzly rescue overall and MARK Gekko anchor point and/or MARK Boa tape sling.

